MAX

Realtime messaging and activity stream engine

Carles Bruguera (@sunbit) Víctor Fernández de Alba (@sneridagh)

Víctor

- Senior Python Developer and IT architect
- Plone Foundation member
- Plone core developer since 2010
- Author of Plone 3 intranets book (2010, PacktPub)



Carles

- Python and JavaScript lover
- Working with python for the last 8 years
- Occasional Erlang coder (when on drugs)
- Regex freak

Python @UPCnet and @BarcelonaTech







UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH

DEMO!

History

- First commit on August, **2011**
- Initially designed as the key feature for the Universitat Politècnica de Catalunya (BarcelonaTech) university concept of social intranet
- Today, MAX is used by more than 30.000 students and 8.000 university staff integrated in the online campus and the institutional collaboration tools

What is MAX?

- RESTful API
- 88 (and growing) endpoints
- Multi-source user and application activity stream
- Asynchronous **messaging** and **conversations**
- GPL Licensed

Old styled forums

Forum Topic Post Post

Post

phpBB yourdomain.com Gilearth. Searth Deard Index - Nate Topic - Fiel part of topic (Duer Control Panel (8 new messages) - View your posts C(14q [[Members () Lagout [Sphost]

(Roderator Control Panel)

Fist part of topic

NEWTOPIC# Search this forum. Search

Mark topics read + 6 topics + Page 1 of 1 (P) Topics are also known as threads (this has a report) W 3 by Pyhost on Sun Sep 14, 2008 10-07 am () A thread with a pull by Aghenet G on then thep 14, 2008 10:12 are 0 2 by Fghant on San Sap 14, 2008 10-12 am (If the topic 00 (part II) by Typical on the topic 10 (and 10) by Aghout G on Dun Dep 14, 2008 10:10 are Ċ. 1 (P) Other topics 00 by Pphead on Sun Sup 14, 2008 10:01 am by Pahant G on Sun Sep 14, 2008 10-09 am 0 Another topic to Tabout on Sun Sep 14, 2008 18-07 am by Refeat G an Burn Bay 14, 2008 10-07 are 0 1 First Topic by **Zghout** G on But Base 14, 2008 10-04 are . . by Palant on Sun Sap 14, 2008 10:00 am

Display topics from previous (Bill Tegics + Sort by Post time + Descending + Oa

NEWTOPIC #

4 Return to Board Index

Mark topics read + 5 topics + Page 1 of 1

Jump Inc Fist part of topic . 06

THE REPORT OF

Users browning this forum: Palaest and 0 quests

FORUM PERMITAGENE

You can post new topics in this forum The case reply to topics in this forum. You can all your posts in this forum. You can delete your posts in this forum. You can post attachments in this forum.

O Board index 12 Subscribe forum

The team + Delete all board cookies + All times are UTC





Asserted by physics @ 2000, 2003, 2005, 2007 physics drough

What is a context?





Contexts

- Identified by unique URIs
- Permissions per context

0	read	0	invite
0	write	0	kick
0	subscribe	0	delete
0	unsubscribe	0	flag

- Multiple context types based on permissions variations
- Granular permissions per user
 - Overriding the default ones defined by the context
 - Grant / Revoke

Real life examples

Communities site

Institutional events

Institutional news

Alumni

Sell your stuff

Online campus

Applied maths III

Signal theory

Compilers

Faculty news

Real life examples (II)

Community types



Open

Closed

Everyone can join and leave at will The owner should invite me to join and I can leave at will

Institutional

The site admin subscribes people, no one can leave



- Stores activity from users and applications
- Usual **social** actions
 - Comments
 - Likes
 - \circ Favorites
- Images and files support



- Realtime conversations and private messaging
- One to one
- Groups
- Images and files support

JS Javascript UI widget



Qe0 comentaris ☆ favorit @ m'agrada P: destacada



• Platform specific **push** notifications



- Internal notifications
 - Double check
 - \circ others





Fully deployable on premises

- Addresses any **security** concerns
- Absolute customer data privacy and ownership
- "Corporate whatsapp"

Features Summary



Components overview



Osiris



- Minimal OAuth2 server implementation
- Build on top of pyramid
- Resource Owner Credentials Flow
- Tokens stored on MongoDB
- /token endpoint to generate token for a user
- /checktoken endpoint to verify a token
- Base LDAP user storage implementation
- Pluggable repoze.who based alternative user storage implementations

MAX



- REST(ful) api
- Also build on top of pyramid
- Hybrid URL-dispatch + traversal routing
- ACL policy with fine-grained permissions per endpoint
- Customized venusian decorator to configure endpoints
- Tweens used for several tasks
- Per-exception catching to provide detailed JSON error messages
- Per-request caching of variables

MAX (Routing)

• Route definition

```
RESOURCES['avatar'] = dict(route='/people/{username}/
avatar', filesystem=True, category='User', name='User
avatar', traverse='/people/{username}')
```

• Endpoint definition

```
@endpoint(route_name='avatar', request_method='POST',
permission=modify_avatar)
def postUserAvatar(user, request):
    """
    Upload user avatar
    """
```

MAX (Tweens)

- exception catcher
- post tunneling
- compatibility check

```
def compatibility checker factory (handler, registry):
       def compatibility checker tween(request):
           requested compat id = request.headers.get('X-Max-Compat-ID', None)
          if requested compat id is None:
               response = handler(request)
               return response
          expected compat id = str(request.registry.settings.get('max.compat id'))
          if expected compat id == requested compat id:
               response = handler(request)
               return response
           else:
               return JSONHTTPPreconditionFailed(
                   error=dict(
                       objectType='error',
                       error="CompatibilityIDMismatch",
                       error description='X-Max-Compat-ID header value mismatch, {} was
expected'.format(expected compat id)))
      return compatibility checker tween
```

MAX (Exception handling)

• Known error use cases are raised as custom exceptions:

raise ObjectNotFound("User {} doesn't have role {}".format(user, role))

• And rendered as a JSON message

@view_config(context=ObjectNotFound)
 def object_not_found(exc, request):
 return JSONHTTPNotFound(error=dict(objectType='error',
error=ObjectNotFound.__name__, error_description=exc.message))

• Non-handled exceptions are logged with request information



Navigation

- 2 Dashboard
- 📥 Users
- Q Contexts
- Api

A Exceptions

Exception hash: df97a345acbc35f85337f1679e2c264e882a6b08

Raised on: 2015/07/21 11:27:46

POST /tokens HTTP/1.0 Accept-Encoding: gzip Connection: close Content-Length: 0 Content-Type: application/json Host: max.upc.edu User-Agent: Dalvik/2.1.0 (Linux; U; Android 5.1.1; Nexus 4 Build/LMY47V) X-Forwarded-For: 147.83.182.8 X-Max-Compat-Id: 2 X-Oauth-Scope: widgetcli X-Oauth-Scope: widgetcli X-Oauth-Username: marc.calvet X-Virtual-Host-Uri: https://max.upc.edu

Traceback (most recent call last):

<pre>File "/var/max.upc.edu/upc/mggs/max-5.3.2-py2.7.egg/max/tweens.py", line 125, in compatibility_checker_tween response = handler(request) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 155, in post_tunneling_tween response = handler(request) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 175, in deprecation_wrapper_tween return response_wrapper(response) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/deprecations.py", line 256, in wrapper response.body = json.dumps(request.actor.getInfo()) File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 91, in excview_tween response = handler(request)</pre>	
<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 155, in post_tunneling_tween response = handler(request) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 175, in deprecation_wrapper_tween return response_wrapper(response) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/deprecations.py", line 256, in wrapper response.body = json.dumps(request.actor.getInfo()) File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/max.upc.edu/upc/mggs/max-5.3.2-py2.7.egg/max/tweens.py", line 125, in compatibility_checker_tween response = handler(request)</pre>	
<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 175, in deprecation_wrapper_tween return response_wrapper(response) File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/deprecations.py", line 256, in wrapper response.body = json.dumps(request.actor.getInfo()) File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 155, in post_tunneling_tween response = handler(request)</pre>	
<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/deprecations.py", line 256, in wrapper response.body = json.dumps(request.actor.getInfo()) File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/tweens.py", line 175, in deprecation_wrapper_tween return response_wrapper(response)</pre>	
<pre>File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/max.upc.edu/upc/eggs/max-5.3.2-py2.7.egg/max/deprecations.py", line 256, in wrapper response.body = json.dumps(request.actor.getInfo())</pre>	
<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/python/python2.7/lib/python2.7/json/initpy", line 243, in dumps return _default_encoder.encode(obj)</pre>	
<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(0, 0) File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(0) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 207, in encode chunks = self.iterencode(o, _one_shot=True)</pre>	
<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable") ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable</pre>	<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 270, in iterencode return _iterencode(o, 0)</pre>	
ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable	<pre>File "/var/python/python2.7/lib/python2.7/json/encoder.py", line 184, in default raise TypeError(repr(o) + " is not JSON serializable")</pre>	
	ypeError: datetime.datetime(2014, 7, 17, 6, 56, 30, 901000) is not JSON serializable	

RabbitMQ & messaging



- Exchange-to-exchange routing
- STOMP over WS using rabbitmq plugins
- "Public" end-user stomp endpoints
- Message delivery and security through routing key bindings
- Oauth authentication via erlang plugin
- Easy plug-in of temp queues for debugging

Messaging Design



MaxCarrot

```
{"uuid": "005fab55bee84",
"user": {
   "username": "johndoe",
    "displayname" : "John Doe"
 },
"action": "add",
"object": "message",
"data": {
    "text": "Hello world!"
 },
"source": "ios",
"domain": "demo",
"version": "4.0.1",
"published": "2015-07-21"}
```

MaxCarrot

- JSON based message format
- Used on messages routed through RabbitMQ
- Packed and unpacked versions
- Metadata/debugging fields
- Purpose related fields
- Encapsulates messaging logic

MaxCarrot

(Rules)

- Map field combinations to actions
- Pack messages following spec
- Ignore any message not matching any mapping

```
"source": {
   "id": "s",
   "type": "char",
   "values": {
       "ios": { "id": "c" },
       (...)
       "max": { "id": "m" }
   }
}
```

```
"version": {
   "id": "v",
   "type": "string",
}
```

MaxCarrot (human-readable)

```
{"uuid": "005fab55bee84",
"user": {
    "username": "johndoe",
    "displayname" : "John Doe"
 },
"action": "add",
"object": "message",
"data": {
    "text": "Hello world!"
 },
"source": "ios",
"domain": "demo",
"version": "4.0.1",
"published": "2015-07-21"}
```

MaxCarrot (nerd-readable)

```
{ 'a':'a','d':
{ 'text':'Helloworld
!'},'g':'005fab55be
e84','i':'demo','o'
:'m','p':'2015-07-2
1','s':'i','u':
{ 'u':'johndoe','d':
'JohnDoe'},'v':'4.0
.1'}
```



MaxBunny

- Pluggable multiprocess domain-aware queue consumer
- A multiprocess runner runs N process for each consumer defined.
- Each consumer binds to a queue and consumes messages
- Runner provides a shared pool of WSGI MaxClient instances, one for each domain.

MaxClient

- Opinionated Wrapper for REST api's
- Wraps endpoint resources based on endpoint list definition. RESOURCES['activity'] = dict(route='/people/{username}/activities')
- Accesses endpoints in a pythonic way

>>> client.people['username'].activities.get(qs={'limit':2})

Creates json bodies from "nested" kwargs (with optional sensible defaults)

MaxClient

- Raises a custom RequestError exception on 5xx and 4xx responses
- Returns None on 404 responses
- Returns parsed JSON body on success responses

WSGI MaxClient

- WSGI version
- Subclassed MaxClient that makes calls to a "fake" wsgi server
- Actual MAX Codebase is run by the client
- Requests don't stress main api servers, only database
- Limitations:
 - User must have privileges on "real" max server
 - Computer from where client is run must have access to storage backed

Twitter external aggregation

- Backend process listens twitter streaming service
- Selected tweets are queued and processed
- Valid tweets are injected into max activity stream
- Max users linked with twitter usernames
- Aggregation of content as a context

Current integrations

UPCnet uLearn Communities

UPCnet uLearn Campus

iOS & Android apps





campus.upcnet.es/course/view.php?id=6

👓 🗢 movistar 😨

12:33

Stream



Otero Hernandez Javier

O 10 minutes ago
P EuroPython demo
Hello guys, just say a big hello to...



20

20



ŵ

☆

* 78% 🗔



Riba Santos Corina © 12 minutes ago ♥ EuroPython demo I'm in! Count on me!



Diaz Bertolez Roberto

O 17 minutes ago
O EuroPython demo
Yeah! Maybe we can celebrate it...

的

00



Pilar Marinas

O 18 minutes ago
 O EuroPython demo
 Just joined to this community and...







Subscription





🕴 77 % 🗔 🗋

Chats



Otero Hernandez Javier () less than a minute ago See you tomorrow!



Janet Durà Pipó © 2 minutes ago I'm so tired...



Carles Bruguera A © 4 minutes ago Just a test for the demo!



O 4 hours ago



Marcos Montero Torres O March 6, 2015 Donde estáis?



Chats









Subscription

More



Víctor Fernández de Alba

② 11 desembre Consultoria

Taller comunitats Nexus 24. Abigail on fire! Gogogo



1

🗩 1

Laura Requena | laura.requena O 11 desembre Hi ha quorum!!!



Oriol B.

eo, canvia't la foto! que amb la nova versió ja no surt pixelada

17/07/14







Potential integrations

<place your web|app|whatever thingy name here>



Whishlist

- Social interactions (Follow/share)
- Finish & polish documentation
- Microservices / Dockerization
- Redis backed cache
- RabbitMQ SSL without NGINX
- Python3 / asyncio
- Explore JSON-LD (HATEOAS)
- Encryption

Community building?

Absolutely! Let's do it!

Contact us, PR are welcome!

Resources

https://upcnet.github.io/max

https://github.com/UPCnet/max

https://github.com/UPCnet/maxserver

Thanks / Gràcies

@sunbit @sneridagh